



## MEINERTZ Finned Tubes

### Uses

MEINERTZ Finned Tubes can be mounted either to be a part of the architectural expression or as a discreet integrated solution. The tubes can be used to prevent cold draught at large glazing units, to heat up botanical houses, industrial buildings, office buildings, etc. Numerous solutions are possible.

### Designation

MEINERTZ Finned Tubes are delivered in different types and models. Please visit [www.meinertz.com](http://www.meinertz.com) for more information, which can be found under the documentation section.

Type-Model-Length  
Example LKK K33-73-08

The code indicates that the type is LKK meaning concentrically welded tappings at each end. K33-73-08 indicates the size of the tube:  
33 = Outside diameter of tube (mm)  
73 = Fin diameter (mm)  
08 = Fin pitch (mm)

### Production

MEINERTZZ Finned Tubes are manufactured by helically fixing a metal strip on to the tube. The lower part of the fin is corrugated which increases the surface and creates a turbulent air flow increasing the output.

### Product

MEINERTZ Finned Tubes can be delivered in 8 different sizes with a fin diameter from 73 to 164mm. Numerous types for wall and floor mounting are available, but also 2 or more tubed elements can be made. Also the MEINERTZ Finned Tubes can be curved to fit a shape of a building. All tubes are produced according to order and come in a maximum length of 6000mm.

### Mounting

The MEINERTZ Finned Tubes can be mounted on the floor or on the wall, but also at the ceiling and in trenches.

### Weight

Find the weight of the different tubes on [www.meinertz.com](http://www.meinertz.com).

### Output

Read more on [www.meinertz.com](http://www.meinertz.com)

### Airvent

1/8" airvent is mounted on the tubes.

### Surface finishing

The MEINERTZ Finned Tubes are supplied powder coated in RAL 9016 as a standard. Other colours are available at an extra surcharge.

### Packaging

MEINERTZ Finned Tubes are carefully packaged in strong cardboard and wrapped in PE sheeting.

### Warranty

A five-year guarantee against defects in materials or workmanship is offered, provided that the unit has been correctly handled and installed.

### Maintenance

Cleaning may be performed with ordinary cleaning agents that do not contain abrasive. Scratches or damages to the surface lacquer may be repaired using traditional spray paint, or by hand-painting with a thin brush.