



MEINERTZ Church Convectors

Applications

It is possible to hang the heater under church pews, so that an even and comfortable heat is established in the church room.

Customized solutions

MEINERTZ church convector is the most flexible, discreet and aesthetic convector for mounting under church pews. It is high-performance and is produced with the taps required to meet the requirements for the renovation of listed buildings. At the same time, they can be delivered in all colors, and thus discreetly integrated into the construction of the bench.

Product

MEINERTZ church convectors are based on MEINERTZ SkyLine, which is made of 70 x 11 x 2.0 mm pressure-stable steel pipes. They are placed at a distance of 13 mm without welded metal plates between the water-carrying pipes. Examples of specifications are:

Type	Height (mm)	Depth (mm)
SL04	70	83
SL07	70	155
SL06	70	131
SL011	70	251
DSL07	140	155

Other models and specifications can be used. MEINERTZ advises on choosing the right convector.

Optimized piping

Optimized piping is created by establishing forced water flow via integrated partitions. In addition, reciprocating runs are kept on the same side. This means that the piping is optimized and can be kept e.g. along the walls. Furthermore, several individual units can be connected while running back and forth along the walls. Thus, there are no unnecessary pipes to deal with. MEINERTZ has also developed various solutions to hide piping and achieve invisible connection.

Customized church pews

MEINERTZ has a standardized pew bracket, which can often be used - and otherwise we develop a special one for the individual project, where the bracket is adapted to the construction of the pew.

Dimension

Depth: n of tubes x (13 + 11) - 13 mm
 Height: 70 or 140 mm
 Length: Max 6000 mm
 Production on special dimensions is possible.

Surface treatment

Available in optional RAL color, without surcharge. It is possible to get the convectors so that they are adapted to the color of the pews.

Guarantee

A 5-year warranty on manufacturing and material defects is provided, subject to proper treatment and installation. We reserve the right to make design and dimensional changes due to technical developments.

Maintenance

Extremely easy to clean. Can be cleaned with a regular detergent that does not contain abrasive. Scratches and damage to the surface of the paint can be repaired with traditional wet paint in a spray can or applied with a thin brush.

Counseling

MEINERTZ follows the entire process from idea stage to design over execution phase and all the way to the final submission. The extensive experience with deliveries to church buildings - gained over many years with deliveries to both home and abroad provides a safe and secure process.

MEINERTZ A/S

Sverigesvej 16 · DK - 8700 Horsens
 Phone +45 8652 1811 · www.meinertz.com